

TABLE OF CONTENTS

DETAIL

OUTSULATION PLUS MD SYSTEM	OPMD 0.0.01M
OUTSULATION PLUS MD SYSTEM STARTER BOARD OPTION	OPMD 0.0.01aM
OPENING PREPARATION- BACKSTOP® NTX	OPMD 0.0.02M
OPTION OPENING PREPARATION-	OPMD 0.0.03M
AQUAFLASH® SYSTEM OPTION	OPMD 0.0.04M
OPENING FLASHING INTEGRATION INSIDE/OUTSIDE CORNERS	OPMD 0.0.05M
OUTSIDE CORNER - HIGH IMPACT	OPMD 0.0.06M
GRADE TERMINATION WITH DRAINAGE STRIP	OPMD 0.0.07M
GRADE TERMINATION WITH DRAINAGE TRACK	OPMD 0.0.08M
TERMINATION AT CONCRETE CURB PREPARATION AT	OPMD 0.0.09MEPS OPMD 0.0.10M
WALL PENETRATIONS	
STOREFRONT WINDOWSILL - JAMB	OPMD 0.0.11M
SELF FLASHING WINDOW SILL - JAMB	OPMD 0.0.12M
STOREFRONT WINDOW HEAD	OPMD 0.0.13M
HEAD J-TRACK OPTION	OPMD 0.0.14M
TERMINATION AT WOOD FRAMED DECK	OPMD 0.0.15M
TERMINATION AT WATERPROOF DECK	OPMD 0.0.16M
PREPARATION AT PARAPET/ WALL INTERSECTION	OPMD 0.0.17M
TERMINATION AT PARAPET - CAP FLASHING	OPMD 0.0.18M
TERMINATION AT PARAPET - ROOF FLASHING INTEGRATION	OPMD 0.0.19M
TERMINATION AT ROOF GRAVEL STOP	OPMD 0.0.20M
TERMINATION AT SLOPED ROOF	OPMD 0.0.21M
VERTICAL WALL/ SUSPENDED SOFFIT TRANSITION	OPMD 0.0.22M
TRANSITION AT SOFFIT/ FASCIA INTERSECTION	OPMD 0.0.23M
FASCIA/ UNINSULATED SOFFIT TRANSITION	OPMD 0.0.24M
HORIZONTAL JOINT - SUBSTRATE CHANGE	OPMD 0.0.25M
HORIZONTAL TERMINATION AT STONE VENEER	OPMD 0.0.26M
HORIZONTAL TERMINATION AT STUCCO	OPMD 0.0.27M
VERTICAL EXPANSION JOINT- EIFS	OPMD 0.0.28M
MASONRY CONTROL JOINTS	OPMD 0.0.29M
VERTICAL EXPANSION JOINT - FLUSH AND RECESSED OPTIONS	OPMD 0.0.30M

DETAIL

VERTICAL EXPANSION JOINT - DOUBLE SEAL OPTION	OPMD 0.0.31M
VERTICAL TERMINATION AT STONE VENEER	OPMD 0.0.32M
PENETRATIONS	OPMD 0.0.33M
SIGN ATTACHMENT	OPMD 0.0.34M
AESTHETIC REVEALS	OPMD 0.0.35M
RECESSED GRAPHICS	OPMD 0.0.36M
PROJECTING GRAPHICS	OPMD 0.0.37M

NOTE

DRYVIT MAKES NO REPRESENTATION REGARDING CONFORMITY OF ITS SUGGESTIONS TO MODEL BUILDING CODES, ENGINEERING CRITERIA, SPECIFIC APPLICATIONS, OR PROJECT LOCATIONS. ALL COMPONENTS INDICATED IN ILLUSTRATIONS, AS WELL AS OTHERS THAT MAY BE REQUIRED FOR THE INTEGRITY OF THE SYSTEM SHALL BE DESIGNED, DETAILED, AND ENGINEERED BY REPRESENTATIVES OF THE ARCHITECT, OWNER, OR CONTRACTOR TO BE IN CONFORMANCE WITH MODEL CODES, ARCHITECTURAL, AND ENGINEERING REQUIREMENTS PERTAINING TO SPECIFIC BUILDING PROJECTS.

DRYVIT MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ARCHITECTURAL DESIGN, ENGINEERING, OR WORKMANSHIP OF PROJECTS UTILIZING DRYVIT SYSTEMS OR PRODUCTS.

THE LIABILITIES OF DRYVIT SHALL BE AS STATED IN THE OUTSULATION PLUS MD SYSTEM LIMITED COMMERCIAL WARRANTY. CONTACT DRYVIT FOR A FULL AND COMPLETE COPY OF THE WARRANTY.

Outsulation® Plus MD System®

The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. Use of a functionally equivalent detail does notice. Contact Dryvit to ensure you have the most recent version.

