

- APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD OR STANDARD PLUS MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
- DETAIL DOES NOT APPLY TO CANTILEVERED DECKS. CANTILEVERED DECKS REQUIRE JOB SPECIFIC FLASHING DETAILS
- DRYVIT GENESIS® OR GENESIS DM BASE COAT IS REQUIRED FOR MECHANICALLY FASTENED SYSTEMS 1-3.
- FASTENERS ARE NOT REQUIRED FOR SYSTEMS 4 OR 5.
- LIEU OF THE DRYVIT DRAINAGE STRIP, HOWEVER, IF PROJECT IS DEFINED AS NON-COMBUSTIBLE. DRAINAGE TRACK USAGE IS LIMITED TO THE BASE OF THE SYSTEM AT FINISHED GRADE LEVEL. WHEN USING DRAINAGE TRACK, BACK OF EPS WILL NEED TO BE NOTCHED TO ACCOMODATE THE DRYVIT DRAINAGE MAT AND WATER-RESISTIVE BARRIER.
- REFER TO PRODUCT DATA SHEETS FOR SPECIFIC APPLICATION METHODS.

BACKSTOP® FLASH AND FILL

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the Mexicological Project of the project using the Dryvit and Tremco products are the BACKSTOP® NTX™ AWRB.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the Mexicological Project using the Dryvit and Tremco products are the BACKSTOP® NTX™ AWRB.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the design of the project using the Dryvit and Tremco products are the BACKSTOP® NTX™ AWRB.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the BACKSTOP® NTX™ AWRB. is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

Outsulation<sup>®</sup> RMD System<sup>™</sup>



Detail: Termination at Wood Framed Deck Checked by: CS Drawn by: HDE Scale: NTS Date: 5/19/2023 www.tremcocpg.com

O-RMD 21

File Name:

