



THIRD-PARTY INSPECTION GUIDELINES FOR OWNERS AND GENERAL CONTRACTORS/CONSTRUCTION MANAGERS

DS150

SECTION ONE

A. Objective

The objective of this guide is to provide Owners and General Contractors/Construction Managers with guidelines for Third Party Inspections that may be required by the building code for installation of Dryvit EIFS or products. This guide may also be used where inspections are not required by the building code, but the Owner or General Contractor/Construction Manager elects to hire a Third-Party Inspector to oversee the installation of Dryvit EIFS or products. Independent Third-Party Inspectors are engaged by Owners or General Contractors/Constructions Managers and are not agents of Tremco Construction Products Group (CPG) These guidelines are not requirements of Dryvit, but are intended to inform Owners, General Contractors/Construction Managers and independent Third-Party Inspectors about the installation of Dryvit EIFS and to aid in the inspection process. These guidelines are not requirements of Tremco CPG Inc., but rather are intended to inform Owners, General Contractors/Construction Managers, and independent Third-Party Inspectors about the installation of Tremco Dryvit brand EIFS, and to aid in the inspection process. Nevertheless, it is solely the duty of the Owners, General Contractors/Construction Managers, and independent Third-Party Inspectors to ensure that the Tremco Dryvit brand EIFS has been properly inspected in accordance with any federal, state, and local laws and regulations, and in accordance with industry standards. These guidelines were prepared by Tremco CPG Inc. in good faith and should not be interpreted as creating any responsibility, warranty, guarantee or liability for Tremco with respect to the use, design, installation or Third-Party Inspection of any specific project. Although sections of these guidelines deal with sealants and flashing, sealants and flashing are not part of the Tremco Dryvit brand EIFS, and Tremco, by issuing these guidelines, shall not have any responsibility or liability for, nor makes any warranty or guarantee with respect to, sealants or flashing material or their installation, unless the parties otherwise agree. Tremco Dryvit brand EIF systems covered by the guidelines include:

| <u>System</u>                           | <u>Specification</u> | <u>Application Instructions</u> | <u>Installation Details</u> |
|---|----------------------|---------------------------------|-----------------------------|
| Owsulation® System                      | DS118                | DS204                           | DS107                       |
| Owsulation® Plus MD System®             | DS137                | DS218                           | DS110                       |
| Owsulation® Plus MD Securock ExoAir 430 | DS902                | DS901                           | DS903                       |
| Owsulation® MD System®                  | DS168                | DS169                           | DS167                       |
| Owsulation® MD Securock ExoAir 430      | DS906                | DS905                           | DS907                       |
| Owsulation® LCMD Systems 1-5™           | DS171                | DS172                           | DS170                       |
| Owsulation® PE System                   | DS943                | DS845                           | DS846                       |
| Owsulation® PE Securock ExoAir 430      | DS914                | DS913                           | DS915                       |
| Owsulation® RMD™                        | DS155                | DS143                           | DS106                       |
| Owsulation® X System                    | DS835                | DS836                           | DS837                       |
| Owsulation Masonry Veneer System        | DS977                | DS976                           | DS978                       |
| Owsulation® HDCI™ System                | DS864                | DS865                           | DS866                       |

## B. Quality Policy

Dryvit is dedicated to manufacturing the highest quality material without compromise. The Third-Party Inspector should assure that all Dryvit products used, and their installation, conform to the contract documents. The Third-Party Inspector should be aware of the objective and quality standards so the completed project will perform as designed.

## C. Third Party Inspector Qualifications

1. The Third-Party Inspector should be knowledgeable in the construction industry.
2. The Third-Party Inspector should be knowledgeable in the installation of Exterior Insulation and Finish Systems (EIFS).
3. The Third-Party Inspector should have attended a training session provided by AWCI and should possess an AWCI/EIFS Inspector Training Certificate.
4. The Third-Party Inspector should be capable of reading and understanding blueprints as well as architectural details. He/she should be able to resolve discrepancies between project conditions and the project design requirements in a timely manner so as not to delay the construction schedule.
5. The Third-Party Inspector should report all discrepancies and nonconforming work to the Owner, Architect, General Contractor/Construction Manager and EIFS Applicator.

## D. Inspections

Inspections should be conducted by the Third-Party Inspector in the spirit of teamwork, cooperation, and assistance in an effort to provide the Owner with a quality installation of the Dryvit EIFS.

Inspections should be conducted at the various stages in the progress of installation. Any deviations from the contract documents and/or Dryvit Specifications, Application Instructions and Installation Details should be reported to the EIFS Applicator, General Contractor/Construction Manager, Architect and Owner by the Third-Party Inspector. All deviations should be corrected by the EIFS Applicator or other appropriate subcontractor prior to proceeding with the next stage of installation. The Third-Party Inspector should confirm that the deviation was corrected and conforms with the contract documents.

## E. Frequency of Inspections (Suggested)\*

1. Field/Panel Application
  - a. Weekly - By the independent Third-Party Inspector.
  - b. Weekly - A joint inspection by the independent Third-Party Inspector, EIFS Applicator, and the General Contractor/Construction Manager.
2. Field Inspection
  - a. Inspections should be conducted by the Third-Party Inspector according to Section One, Paragraph E.1. Additionally, inspections should be conducted during and after completion of each application phase. Various phases of application are defined as follows:
    - 1) Material storage
    - 2) Inspection of installed substrates
    - 3) Moisture protection of substrate (if applicable)
    - 4) Installation of drainage medium (if applicable)
    - 5) Inspection of flashing (supplied by others)
    - 6) Installation of insulation board
    - 7) Application of base coat and reinforcing mesh
    - 8) Application of finish coat or masonry veneer as specified
    - 9) Application of sealants (supplied and installed by others)
  - b. The Third-Party Inspector should complete an Inspection Report (see Section Two) and the Inspection Checklist Work Sheet (See Section Three) during each inspection of the project.
3. Final Inspection
  - a. A final inspection of the project should be conducted jointly by the Owner, Third Party Inspector, General Contractor/Construction Manager, and EIFS Applicator for the purpose of final review and acceptance of the work by the Owner.

- b. Each of the above parties should acknowledge in writing acceptance of the completed Dryvit system application prior to request for and issuance of the Dryvit Warranty, if any. The Third-Party Inspector should complete the Third-Party Inspection Certificate (see Section Four) certifying that the inspections were completed in accordance with the contract documents. A copy of the completed Inspection Certificate, Inspection Reports, and Checklist Work Sheets should be forwarded to:

Dryvit  
3735 Green Road Beachwood, OH 44122 (401) 822-4100 Attn: Warranty Services

\*The Owner may require that the Third-Party Inspector inspect the project more frequently than listed. This should be agreed upon between the Owner and the Third-Party Inspector.

---

Dryvit  
3735 Green Road  
Beachwood, OH 44122  
www.dryvit.com

Information contained in this document conforms to the standard detail recommendations and specifications for the installation of Dryvit products as of the date of publication of this document and is presented in good faith. Dryvit assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Dryvit.



For more information on [Dryvit Systems](#) or [Continuous Insulation](#), visit these

**SECTION TWO**

**THIRD-PARTY INSPECTION REPORT**

**File No.:** \_\_\_\_\_

**Date:** \_\_\_\_\_

**Project Name/Address**  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Applicator Name/Address**  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Certificate No.:** \_\_\_\_\_

**Type of Dryvit System:**

- Otsulation®
- Otsulation® Plus MD System®
- Otsulation® Plus MD Securock ExoAir 430
- Otsulation® MD System®
- Otsulation® MD Securock ExoAir 430
- Otsulation® PE System
- Otsulation® PE Securock ExoAir 430
- Otsulation® LCMD™ Systems
  - System 1
  - System 2
  - System 3
  - System 4
  - System 5
- Otsulation® RMD™ System
- Otsulation® X System
- Otsulation Masonry Veneer System
- Otsulation® HDCI System
- Otsulation® HDCI Securock ExoAir 430

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Inspections Made:**

- Material Storage
- Substrate Inspection
- Air/Water-Resistive Barrier
- Installation/Application
- Drainage Medium
- Insulation Board Installation
- Application of Base Coat and Reinforcing Mesh
- Application of Finish Coat or Masonry Veneer
- Application of Sealants
- Application of Flashing

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

List items requiring correction, corrections of previously listed findings, and previously listed uncorrected findings:

| Finding | Report Ref./Date | Correction | Complete |
|---------|------------------|------------|----------|
| _____   | _____            | _____      | _____    |
| _____   | _____            | _____      | _____    |
| _____   | _____            | _____      | _____    |

**Comments:** \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

To the best of my knowledge, work inspected was in accordance with the project specification and latest Dryvit \* \_\_\_\_\_ System Specifications, dated \_\_\_\_\_, Application Instructions, dated \_\_\_\_\_, and Installation Details, dated \_\_\_\_\_, except as noted above. In case of discrepancy between the Specifications, Application Instructions and Details, and Dryvit's suggested Specifications, Application Instruction and Details for the system being installed, the third-party inspector shall have the design professional confirm in writing which documents apply.

\* Fill in name of system.

**Signed:** \_\_\_\_\_  
**Date:** \_\_\_\_\_  
**Print Full Name:** \_\_\_\_\_  
**Company Name:** \_\_\_\_\_  
**Address:** \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
**Telephone:** \_\_\_\_\_  
**E-Mail Address:** \_\_\_\_\_

**SECTION THREE**

**INSPECTION CHECKLIST WORKSHEET**

This section should be completed each time the Third-Party Inspector visits the project site. Attach to Section Two at the completion of each visit.

**A. Weather (Field Application Only)**

1. Temperature: \_\_\_\_\_ at \_\_\_\_\_ AM \_\_\_\_\_  
\_\_\_\_\_ at \_\_\_\_\_ PM \_\_\_\_\_

2. Weather Condition: \_\_\_\_\_

3. 24 hour forecast: \_\_\_\_\_

4. Notes: \_\_\_\_\_  
\_\_\_\_\_

**B. Materials and Storage**

|   | YES   | NO    |
|---|-------|-------|
| 1. All materials stored under cover and protected from weather  | _____ | _____ |
| 2. When outside storage is required   | _____ | _____ |
| a. Materials stacked on the ground  | _____ | _____ |
| b. Temperatures in storage area greater than 40 °F (4 °C) and less than 90 °F (32 °C) (Refer to specific product data sheets) | _____ | _____ |
| 3. Insulation board   | _____ | _____ |
| a. Stored under cover   | _____ | _____ |
| b. Stacked flat   | _____ | _____ |
| c. Not exposed to direct sunlight   | _____ | _____ |

**C. Inspection of Installed Substrate**

|   |              |       |
|---|--------------|-------|
| 1. Substrate type:                                      | _____        |       |
| 2. Thickness of sheathing:                              | _____ inch   |       |
| 3. Framing c to c:                                      | _____ inches |       |
| 4. Date of sheathing installation:                      | _____        |       |
| 5. Correct orientation of sheathing                     |              |       |
| a. Sheathing joints are offset from corners of openings | _____        | _____ |
| b. Edges of sheathing are supported by framing members  | _____        | _____ |
| c. Fastener type and spacing per contract documents     | _____        | _____ |

|  | YES   | NO    |
|--|-------|-------|
| f. Glass-mat gypsum oriented with correct side outward     | _____ | _____ |
| g. Wood-based sheathings properly gapped at edges and ends | _____ | _____ |
| 6. Dimensional tolerance                                   | _____ | _____ |
| a. Flat within 1/4 inch in 4 ft 0 in radius                | _____ | _____ |
| 7. Damage exceeding 3/8 inch                               | _____ | _____ |
| 8. Clean surface, dry, free of contaminants                | _____ | _____ |
| 9. Notes   | _____ |       |
|  | _____ |       |

**D. Air/Water-Resistive Barrier Installation (if applicable)**

|  | YES   | NO    |
|--|-------|-------|
| 1. Trowel, Spray, or Roller Applied Membrane                           |       |       |
| a. Dryvit Grid Tape™ (sheathing applications only)                     |       |       |
| 1) 4 in wide supplied by Dryvit  | _____ | _____ |
| 2) Sheathing joints covered  | _____ | _____ |
| 3) Terminations covered (field and panelized)                          | _____ | _____ |
| 4) Inside and outside corners covered                                  | _____ | _____ |
| 5) Installed at sheathing framing interface for panelized construction | _____ | _____ |
| b. Dryvit Water-Resistive Membrane                                     |       |       |
| 1) Material identification   |       |       |
| a) Manufactured and supplied by Dryvit                                 | _____ | _____ |
| b) Name of product: _____  | _____ | _____ |
| c) Batch number: _____   | _____ | _____ |
| 2) Proper type for installed substrate                                 | _____ | _____ |
| 3) Ambient air temperature: ____ °F or °C                              | _____ | _____ |
| 4) Wall temperature: ____ °F or °C                                     | _____ | _____ |
| 6) Pre-spot fasteners and Grid Tape locations                          | _____ | _____ |
| 7) Continuous layer of membrane applied over entire surface area       | _____ | _____ |
| a) Panelized construction-membrane extended onto framing members       | _____ | _____ |
| 8) Coverage per pail: _____ ft <sup>2</sup>                            | _____ | _____ |

|  | YES   | NO    |
|--|-------|-------|
| <b>c. Dryvit AquaFlash® System</b>                   |       |       |
| 1) 4 in, 6 in or 9 in Mesh                           |       |       |
| 2) AquaFlash Mesh fully embedded in AquaFlash Liquid | _____ | _____ |
| 3) Air and surface temperature: _____ °F or °C       | _____ | _____ |
| 4) Surface is clean, dry and smooth                  | _____ | _____ |

e. Notes \_\_\_\_\_  
 \_\_\_\_\_

**2. Sheet Membranes**

|   |       |       |
|---|-------|-------|
| a. Type of sheet material: _____  |       |       |
| b. Flashing Tape installed as per manufacturer's instructions               | _____ | _____ |
| c. Water-resistive barrier installed horizontally in a weatherboard fashion | _____ | _____ |

**E. Installation of Drainage Medium (if applicable)**

**1. Type of Drainage Medium**

|  |       |       |
|--|-------|-------|
| a. Dryvit Drainage Mat™  | _____ | _____ |
| b. Tyvek Stucco Wrap   | _____ | _____ |
| c. Metal or plastic lath   | _____ | _____ |
| d. MD Spacers™   | _____ | _____ |
| e. Grooved insulation board  |       |       |
| 1) Spacing of grooves c to c   |       |       |
| a) 4 inch (Outsulation LCMD System™ 3)   | _____ | _____ |
| b) 12 inch (Outsulation® MD System®, Outsulation MD Securock ExoAir 430, Outsulation PE System and Outsulation PE Securock ExoAir 430) | _____ | _____ |

    2) Proper width and depth of groove

|   |       |       |
|---|-------|-------|
| <b>2. Drainage medium installed in accordance with contract documents</b> | _____ | _____ |
|---|-------|-------|



YES

NO

F. Insulation Board Inspection/Installation

1. Inspection

a. Supplied by a licensed supplier of insulation board

\_\_\_\_\_

\_\_\_\_\_

b. Proper type of given project

1) Expanded polystyrene (EPS)

\_\_\_\_\_

\_\_\_\_\_

2) Xenergy™ Board (Extruded polystyrene)

\_\_\_\_\_

\_\_\_\_\_

3) Polyisocyanurate

c. Proper packaging

\_\_\_\_\_

\_\_\_\_\_

1) Polyethylene bags (EPS)

\_\_\_\_\_

\_\_\_\_\_

2) Lot number marked on bag (EPS)

d. Proper marking on board (EPS)

\_\_\_\_\_

\_\_\_\_\_

1) Each board edge marked

2) One board each package marked both faces

\_\_\_\_\_

\_\_\_\_\_

e. Dimensional tolerance

1) EPS

a)

1 in-4 in = +/- 1/16 in

\_\_\_\_\_

\_\_\_\_\_

b) Width = +/- 1/16 in

\_\_\_\_\_

\_\_\_\_\_

c) Length = +/- 1/1 in

\_\_\_\_\_

\_\_\_\_\_

d) Squareness < 1/3 in in 1 in

\_\_\_\_\_

\_\_\_\_\_

e) Flatness < 1/32 in in 4 ft – 0 in

\_\_\_\_\_

\_\_\_\_\_

2) Extruded Polystyrene

a) Thickness 1 in, 1 1/2 in, 2 in, 2 1/2 in, 3 in 4 in

\_\_\_\_\_

\_\_\_\_\_

b) Width = +/- 1/16 in

\_\_\_\_\_

\_\_\_\_\_

c) Length = +/- 1/16 in

\_\_\_\_\_

\_\_\_\_\_

d) Squareness < 1/32 in in 12 in

\_\_\_\_\_

\_\_\_\_\_

e) Flatness < 1/32 in in 4 ft – 0 in

f. Notes:

\_\_\_\_\_  
\_\_\_\_\_

2. Installation

a. Date of Installation: \_\_\_\_\_

b. Ambient air temperature: \_\_\_\_\_ °F or °C

c. Wall temperature: \_\_\_\_\_ °F or °C

d. Material Identification – adhesive

1) Manufactured and supplied by Dryvit

\_\_\_\_\_

\_\_\_\_\_

2) Name of product: \_\_\_\_\_

3) Batch number: \_\_\_\_\_

4) Proper type for installed substrate

\_\_\_\_\_

\_\_\_\_\_

|  | YES   | NO    |
|--|-------|-------|
| 5) Mixing proportion   |       |       |
| a) Lump free Type I or II Portland cement  | _____ | _____ |
| b) Clean potable water   | _____ | _____ |
| 6) Notch trowel 3/8 in w x 1/2 in 2 x 1 1/2 in c to c used to apply adhesive               | _____ | _____ |
| 7) Adhesive applied with ribbons running vertically along width of insulation board        | _____ | _____ |
| e. Material identification – mechanical fasteners  |       |       |
| 1) Proper type for system being installed  | _____ | _____ |
| 2) Corrosion resistant fasteners   | _____ | _____ |
| 3) Proper length of fastener   | _____ | _____ |
| 4) Washer plates flush with surface of insulation board                                    | _____ | _____ |
| f. Dryvit Detail Mesh® attached to the substrate for back wrapping at system terminations  | _____ | _____ |
| g. Insulation boards installed with long edges oriented horizontally, – EPS and XPS        | _____ | _____ |
| h. Insulation boards installed in a running bond with vertical joints staggered            | _____ | _____ |
| i. Insulation board joints tightly butted  | _____ | _____ |
| j. Insulation board joints offset from sheathing board joints a minimum of 8 inches        | _____ | _____ |
| k. Insulation board joints at all inside and outside corners are staggered and interlocked | _____ | _____ |
| l. Insulation board cut in an “L” shape piece around all openings                          | _____ | _____ |
| m. Insulation board terminates a minimum of 6 inches above finished grade                  | _____ | _____ |
| n. Insulation board terminates with proper gap at the abutment of dissimilar materials     | _____ | _____ |
| o. Expansion joints positioned at proper locations   | _____ | _____ |
| p. Minimum thickness of insulation board at base of aesthetic reveals is 3/4 inch          | _____ | _____ |
| q. Projecting features incorporate proper slope requirements                               | _____ | _____ |
| r. Projecting features pattern per contract documents                                      | _____ | _____ |
| s. Fasteners installed into framing members or nailable substrate                          | _____ | _____ |
| t. 100% of insulation board (EPS) sanded flat  | _____ | _____ |

|  | YES   | NO    |
|--|-------|-------|
| u. Slivers of insulation board/foam spray installed where required | _____ | _____ |
| Notes:   | _____ |       |
|  | _____ |       |

| G. Application of Base Coat and Reinforcing Mesh   | YES   | NO    |
|--|-------|-------|
| <b>1. Inspection of Installed Insulation</b>   |       |       |
| a. Surface of insulation board has been sanded to remove all irregularities – EPS and XPS            | _____ | _____ |
| b. All insulation boards are tightly butted or filled with insulating material                       | _____ | _____ |
| c. Surface of insulation board is clean, dry, flat and all sanding dust is removed                   | _____ | _____ |
| d. There is no UV damage of insulation board from extended exposure                                  | _____ | _____ |
| e. Damaged insulation board has been replaced  | _____ | _____ |
| <b>2. Base Coat and Reinforcing Mesh Application</b>   |       |       |
| a. Manufactured and supplied by Dryvit   | _____ | _____ |
| b. Name of product: _____  | _____ | _____ |
| c. Batch number: _____   | _____ | _____ |
| d. Proper product for application  | _____ | _____ |
| e. Mixing proportion   |       |       |
| 1) Lump free Type I or II Portland cement  | _____ | _____ |
| 2) Clean potable water   | _____ | _____ |
| f. Type of reinforcing mesh: _____   | _____ | _____ |
| g. Date of installation: _____   | _____ | _____ |
| h. Ambient air temperature: _____ °F or °C   | _____ | _____ |
| i. Wall temperature: _____ °F or °C  | _____ | _____ |
| j. Base coat mixture used to embed previously installed Detail Mesh for back wrapping                | _____ | _____ |
| k. Corner Mesh when specified is embedded in base coat prior to installing overall base coat         | _____ | _____ |
| l. Corners of all openings have additional reinforcement as shown in Dryvit Application Instructions | _____ | _____ |
| m. Base coat applied to wall surface prior to embedding reinforcing mesh                             | _____ | _____ |
| n. Panzer® Mesh installed as first layer (where specified)   | _____ | _____ |
| o. Edges of Panzer Mesh butted tightly, not overlapped   | _____ | _____ |
| p. Panzer Mesh totally embedded in base coat   | _____ | _____ |
| q. Base coat allowed to dry minimum of 24 hours prior to applying second layer                       | _____ | _____ |

|  | YES   | NO    |
|--|-------|-------|
| <b>r. Standard base coat</b>   |       |       |
| 1) Base coat applied to wall surface prior to embedding reinforcing mesh           | _____ | _____ |
| 2) Reinforcing mesh overlapped a minimum of 2 1/2 in at all edges                  | _____ | _____ |
| 3) Applied opposite direction of Panzer Mesh when used as a second layer           | _____ | _____ |
| 4) Offset a minimum of 8 in from Panzer Mesh edges (when applicable)               | _____ | _____ |
| 5) Reinforcing mesh not lapped within 8 in of any corner                           | _____ | _____ |
| 6) Reinforcing mesh continuous through aesthetic reveals                           | _____ | _____ |
| 7) All foam shapes are covered with base coat and reinforcing mesh                 | _____ | _____ |
| 8) Reinforcing mesh is totally embedded. There is no mesh color visible            | _____ | _____ |
| 9) Base coat mixture applied smoothly and free of trowel marks                     | _____ | _____ |
| 10) For panel applications base coat and reinforcing mesh is extended onto framing | _____ | _____ |
| s. Base coat coverage per pail: _____ ft <sup>2</sup>                              |       |       |
| t. Notes: _____  |       |       |

**H. Finish Coat Application**

|   |       |       |
|---|-------|-------|
| <b>1. Inspection of reinforced base coat</b>                                    |       |       |
| a. Base coat free of irregularities   | _____ | _____ |
| b. Base coat clean, dry, free of dust, dirt efflorescence or other contaminants | _____ | _____ |
| c. Base coat has no reinforcing mesh show through                               | _____ | _____ |
| <b>2. Finish coat application</b>   |       |       |
| a. Manufactured and supplied by Dryvit  | _____ | _____ |
| b. Finish type: _____   |       |       |
| c. Batch number: _____  |       |       |
| d. Date of installation: _____  |       |       |
| e. Ambient air temperature: _____ °F or °C                                      |       |       |
| f. Wall temperature: _____ °F or °C   |       |       |
| g. Finish mixed in accordance with Dryvit Application Instructions              | _____ | _____ |
| h. Amount of water added to each pail: _____                                    |       |       |
| i. Spray or trowel applied: _____   |       |       |
| j. Finish applied to proper thickness   | _____ | _____ |
| k. Finish not installed in joints at terminations, expansion, etc.              | _____ | _____ |
| l. All finish material from same batch  | _____ | _____ |

|   | YES   | NO    |
|---|-------|-------|
| m. Texture and color consistent                     | _____ | _____ |
| n. Cold joints                                      | _____ | _____ |
| o. Coverage per 5 gallon paid _____ ft <sup>2</sup> | _____ | _____ |

**3. Masonry Veneer Application**

- a. Masonry Veneer is recognized in a current ICC ES Evaluation Report demonstrating compliance with ICC-ES AC51 Acceptance Criteria for Adhered Manufactured Stone Masonry and ASTM C1670 Standard Specification for Adhered Manufactured Stone Masonry Units
- b. Masonry Veneer is minimum 6mm thick and does not exceed 15 lb/ft<sup>2</sup> (70 kg/m<sup>2</sup>)
- b. Reinforcing mesh is Intermediate Mesh or heavier
- c. Date of installation: \_\_\_\_\_
- e. Ambient air temperature: \_\_\_\_\_ °F or °C
- f. Wall temperature: \_\_\_\_\_ °F or C°
- g. Primus for skim coat and masonry veneer adhesive mixed in accordance with Dryvit Application Instructions
- h. Amount of water added to skim coat
- i. Amount of water added to adhesive
- j. Type of mortar installed
- k. Sealant installed according to manufacturer's instructions

**I. Flashings ()**

|  | YES   | NO    |
|--|-------|-------|
| 1. Flashing at openings installed per contract documents and Dryvit Installation Details       | _____ | _____ |
| 2. Cap flashing installed as soon as practical after installation of Dryvit system             | _____ | _____ |
| 3. Cap flashing sloped toward roof   | _____ | _____ |
| 4. Roof wall intersection diverters are installed per contract and Dryvit Installation Details | _____ | _____ |
| 5. Flashing provided in sections is sealed   | _____ | _____ |
| 6. Flashing extends a minimum of 2 1/2 in over the surface of the Dryvit system                | _____ | _____ |
| 7. Flashing includes a drip edge   | _____ | _____ |
| 8. Exposed vertical leg of flashing is tight against the surface of the Dryvit system          | _____ | _____ |

**SECTION FOUR**

**THIRD PARTY INSPECTION CERTIFICATE**

To (Owner): \_\_\_\_\_

Date: \_\_\_\_\_

Re: Project: \_\_\_\_\_

Address: \_\_\_\_\_

City/State: \_\_\_\_\_

**FINAL INSPECTION REPORT**

Type of Dryvit System:

- Otsulation® \_\_\_\_\_
- Otsulation® Plus MD System® \_\_\_\_\_
- Otsulation® Plus MD Securock ExoAir 430 \_\_\_\_\_
- Otsulation® MD System® \_\_\_\_\_
- Otsulation® MD Securock ExoAir 430 \_\_\_\_\_
- Otsulation® PE System \_\_\_\_\_
- Otsulation® PE Securock ExoAir 430 \_\_\_\_\_
- Otsulation® LCMD™ Systems \_\_\_\_\_
- System 1 \_\_\_\_\_
- System 2 \_\_\_\_\_
- System 3 \_\_\_\_\_
- System 4 \_\_\_\_\_
- System 5 \_\_\_\_\_
- Otsulation® RMD™ System \_\_\_\_\_
- Otsulation® X System \_\_\_\_\_
- Otsulation Masonry Veneer System \_\_\_\_\_
- Otsulation® HDCI System \_\_\_\_\_
- Otsulation® HDCI Securock ExoAir 430 \_\_\_\_\_

This is to certify that I performed an inspection of the Dryvit \_\_\_\_\_ System at the above address.

Based upon my personal observation and written reports of the installation of the Dryvit system, it is my judgment that the inspected installation was performed, to the best of my knowledge, in accordance with the approved plans, the most current Dryvit \_\_\_\_\_ Specifications, dated \_\_\_\_\_, Application Instructions, dated \_\_\_\_\_, and Installation Details, dated \_\_\_\_\_.

Very truly yours,

**Third Party Inspector**

By: \_\_\_\_\_  
Title: \_\_\_\_\_

Date: \_\_\_\_\_

**General Contractor**

By: \_\_\_\_\_  
Title: \_\_\_\_\_

Date: \_\_\_\_\_

**Owner**

By: \_\_\_\_\_  
Title: \_\_\_\_\_

Date: \_\_\_\_\_

**Applicator**

By: \_\_\_\_\_  
Title: \_\_\_\_\_

Date: \_\_\_\_\_

A copy of this certificate should be returned to Dryvit accompanied with the Third-Party Inspection Reports (see Section Two) and Inspection Checklist Work Sheets (see Sec. Three)

DS150  
07.2023

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



[dryvit.com](http://dryvit.com) | 800.556.7752



*Construction Products Group*

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | [tremcocpg.com](http://tremcocpg.com)