



TAFS® OVER ICFs

Transition to Existing Wall

NOTE:

1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD™ OR STANDARD PLUS™ MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DOCUMENTS
2. IT IS THE RESPONSIBILITY OF THE DESIGNER AND CONTRACTOR TO DESIGN AND CONSTRUCT THE WALLS SO THE EXTERIOR FINISH OF BOTH THE ICF WALL AND THE CMU WALL ARE IN THE SAME PLANE
3. THE JOINT BETWEEN THE TWO WALLS MAY OR MAY NOT BE A STRUCTURAL CONNECTION WITH DOWELS AS SPEC'D BY THE STRUCTURAL ENGINEER

The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. Use of a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

