



**DUPONT® TYVEK®
STUCCOWRAP™ OPTION
(SYSTEM 2)**

NOTE:

1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD OR STANDARD PLUS MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
2. THE BASE COAT SHALL BE GENESIS® OR GENESIS DM FOR MECHANICALLY FASTENED SYSTEMS 1, 2, 3.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

Outsulation® RMD System™

| | | | | | | | |
|-------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|----------------|------------|-----------------|------------|--|----------------------------------------------------------------------------------------------------------------------|
|  Dryvit Technical Support: 800-556-7752 | Detail: System 2 Cutaway with Starter Board | | | | File Name: | |  Construction Products Group |
| | Drawn by: HDE | Checked by: CS | Scale: NTS | Date: 5/19/2023 | O-RMD 2a | | |
| www.tremcocpg.com | | | | | | | |