Dryvit Systems, Inc.

One Energy Way West Warwick, RI 02893 (401) 822-4100 ehs@dryvit.com



SAFETY DATA SHEET

Date Issued: July 07,2017

Section 1 - Chemical Product and Company Identification

Product Name: StandardTM Mesh 48, StandardTM Mesh 72, StandardTM Mesh 297, StandardTM Plus Mesh 48, Intermediate® Mesh 48, CornerTM Mesh, Panzer® 15 Mesh, Panzer® 20 Mesh, Sprint® Mesh 7 ½, Ultramesh®, I.S. MeshTM, Detail® Mesh 9 ½, Non-Woven 48 and Softkote Mesh 48"

Chemical Formula: N/A

CAS Number: None

Other Designations: Woven Fiberglass Fabric

General Use: Industrial

Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number	% wt <i>or</i> % vol
Continuous Filament/Fiber Glass	65997-17-3	80.0 - 96.0%
Vinyl Chloride Copolymer	None	4.0-20.0%
Inorganic/Organic Pigments	None	.05-8.0%

Trace Impurities: N/A

	OSH	APEL	ACGI	HTLV	NIOSI	HREL	NIOSH
Ingredient	TWA	STEL	TWA	STEL	TWA	STEL	IDLH
Continuous Filament Fiberglass	15 mg/cuM	N/E	10.0 mg/m ³	N/E	3 Fiber/cc	N/E	N/E
Vinyl Chloride Copolymer Inorganic/organic pigments	N/E	N/E	N/E	N/E	N/E	N/E	N/E

Section 3 - Hazards Identification

Emergency Overview

Coated and finished fabrics are stable under normal ambient conditions.

Potential Health Effects

Primary Entry Routes: Inhalation

Target Organs: None

Acute Effects

Inhalation: Mechanical irritation of the mouth, nose and throat

Eye: Direct contact will cause mechanical irritation.

Skin: Transient mechanical irritation. Occasionally there might be skin irritation noted by individuals who are initially exposed to fiberglass.

Ingestion: Observe individual. If symptoms of GI irritation develop, consult a physician.

Carcinogenicity: IARC, NTP, and OSHA do not list Coated Glass Fabrics as a carcinogen.

Medical Conditions Aggravated by Long-Term Exposure: Skin, eyes and Respiratory Irritation.

Chronic Effects: None Known (See Section 11)

HMIS			
Н	1		
F	0		
R	0		
PPE [†]			
[†] Sec.	8		

Section 4 - First Aid Measures

Inhalation: Remove to fresh air; drink water to clear throat and blow nose to expel fibers. **Eye Contact:** Flush with water for15 minutes; get medical attention if irritation persists.

Skin Contact: Wash with soap and water

Ingestion: Consult a physician if G.I. irritation exists.

Note to Physicians: N/A

Special Precautions/Procedures: None

Section 5 - Fire-Fighting Measures

Flash Point: None

Flash Point Method: N/A

Burning Rate: None Auto-ignition Temperature: None

LEL: None

UEL: None

Flammability Classification: Non-flammable

Extinguishing Media: Water is the best extinguishing media. Or use that which is appropriate for the surrounding area.

Unusual Fire or Explosion Hazards: None

Hazardous Combustion Products: Any sizing, binders or coatings on the fiberglass fabric might form hazardous decomposition products during a sustained fire. Follow fire-fighting procedures and use proper fire-fighting equipment. **Fire-Fighting Instructions:** Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face-piece operated in pressure-demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Prevent the spread of fiberglass dust and avoid dust generation conditions. Vacuum clean dusts and fiber. If sweeping is necessary, use a dust suppressant. Those involved in the clean up of fiberglass should use appropriate personal protective equipment. See Section 8.

Containment: N/A

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Handle properly to prevent the spread of fiberglass dust or fibers.

Storage Requirements: Store in proper containers to prevent the spread of dusts and fibers. Low humidity levels will increase the spread of dusts and fibers.

Regulatory Requirements: Keep airborne dusts and fiber concentrations below regulatory levels.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: None

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne dust or fiber concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Respiratory Protection: Where airborne dusts or fibers exceed the TLV, use NIOSH approved respirator to protect against nuisance dusts. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions and levels of airborne contamination.

Protective Clothing/Equipment: If necessary wear protective gloves or use barrier cream to protect against any mechanical irritation. Eye protection is not required unless fiber levels might cause mechanical irritation of the eyes or local regulations require the use of eye protection. Goggles should then be used. Other protective clothing is not required.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. **Contaminated Equipment:** Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash hands after handling this material.



SDS

Section 9 - Physical and Chemical Properties

Physical State: Woven fiberglass fabric Appearance and Odor: no discernible odor Odor Threshold: N/A Vapor Pressure: None Vapor Density (A60 ir=1): N/A Formula Weight: None Density: N/A Specific Gravity (H₂O=1, at 4 °C): N/A pH: 6-8 (In water) Water Solubility: Not soluble Other Solubility's: N/A Boiling Point: N/A Freezing/Melting Point: 800 Deg. C. Viscosity: N/A Refractive Index: N/A Surface Tension: N/A % Volatile: 0% Evaporation Rate: N/A

Section 10 - Stability and Reactivity

Stability: Dryvit Systems, Inc. Coated Glass Fabric is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: None

Conditions to Avoid: None

Hazardous Decomposition Products: Thermal oxidative decomposition of Dryvit Systems, Inc. Coated Glass Fabrics can produce oxides of

carbon, CO, CO2, and hydrocarbons.

Section 11- Toxicological Information

Toxicity Data:*

Fiber Toxicity: Glass Fiber diameter determines whether the fiber is respirable. NOISH has determined that man-made mineral fibers with diameters equal or greater than 3.5 microns are non-respirable. Respirable fibers will penetrate deep into the lungs. All E-glass continuous filament fiberglass has a fiber diameter larger than 3.5 microns and therefore are nonrespirable. **Carcinogenicity:** The following organizations have found that the continuous fiberglass filaments are not considered to be carcinogenic based on human and animal tests conduced within the last 10 years.

Internal Agency for Research on Cancer-IARC

American Conference of Governmental Industrial Hygienists – ACGIH

Occupational Safety and Health Administration - OSHA National Toxicity Program NTP 7th Annual Report on Carcinogens.

Section 12 - Ecological Information

Fiberglass Fabric, cleaned or finished is considered to be an inert solid waste and will not cause harm to the environment if spilled or released. This product is not manufactured with, or does not contain and Ozone Depleting Chemicals.

Section 13 - Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Disposal Regulatory Requirements: N/A Container Cleaning and Disposal: N/A

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101):

- Shipping Name: Fiberglass Fabric Shipping Symbols: None Hazard Class: None ID No.: None Packing Group: N/A Label: None Special Provisions (172.102): None
- Packaging Authorizations
 a) Exceptions: None
 b) Non-bulk Packaging: None
 c) Bulk Packaging: None
- Quantity Limitations
- a) Passenger, Aircraft, or Railcar: None
- b) Cargo Aircraft Only: None
- Vessel Stowage Requirements a) Vessel Stowage: None
- **b) Other:** None

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33) RCRA Hazardous Waste Classification (40 CFR 261.): Not classified CERCLA Hazardous Substance (40 CFR 302.4) listed/unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112 CERCLA Reportable Quantity (RQ), No RQ SARA 311/312 Codes: N/A SARA Toxic Chemical (40 CFR 372.65): Not listed SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed, Threshold Planning Quantity (TPQ): None **OSHA Regulations:** Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed OSHA Specifically Regulated Substance (29CFR 1910.) No **State Regulations:** None

Section 16 - Other Information

Additional Hazard Rating Systems: NFPA Hazard Rating:	Health	-	1
	Flammability	-	0
••••••	Reactivity	-	0
	Unusual Hazards	-	None