



NOTE:

1. LIGHT GAUGE STEEL FRAME SHALL BE DESIGNED FOR SPECIFIC PROJECT LOADS AND CONDITIONS TO MEET LOCAL BUILDING CODES BY LICENSED ENGINEER.
2. APPLY DYMONIC 100 AT 40 MILS 1" (25 MM) MIN. ONTO FACE OF SECUROCK EXOAIR 430 PANEL AND 1-5/8" (41 MM) MIN. ONTO OUTSULITE PANEL EDGE. AT IN-PLANE BOARD JOINTS ENSURE MINIMUM OVERLAP OF 3/4" (19 MM) MIN. AT 40 MILS.
3. OFFSET SECUROCK EXOAIR 430 JOINTS FROM INSULATION BOARD JOINTS BY 8" (203 MM) MINIMUM, HORIZONTALLY AND VERTICALLY.



Dryvit Technical Support: 800-556-7752

The architecture, engineering, and design of the project using the Dryvit Tremco and USG products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit Tremco and USG specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit Tremco and USG to ensure you have the most recent version.

Outsulite® Securock® ExoAir® 430 Panel System



Technical Support: 866-209-2404

Detail: EPS Board Installation

Drawn by: HDE

Checked by:

Scale: NTS

Date: 1/9/2023

File Name:

OSL SE430-4

www.tremcocpg.com

