



NOTE:

1. ROOF ASSEMBLY, SHEATHING AND CAP FLASHING ARE INSTALLED IN THE FIELD AND NOT COMPONENTS OF THE PANEL SYSTEM.
2. EPS THICKNESS IS DICTATED BY LOCAL CODE AUTHORITY AND APPLICABLE TESTING.
3. REFERENCE DS920 FOR APPROVED SEALANTS.
4. DYMONIC 100 AT 40 MILS MAY BE USED IN LIEU OF EXOAIR 110AT.
5. APPLY DYMONIC 100 AT 40 MILS 1" (25 MM) MIN. ONTO FACE OF SECUROCK EXOAIR 430 PANEL AND 1-5/8" (41 MM) MIN. ONTO OUTSULITE PANEL EDGE.
6. DRYVIT REINFORCED BASE COAT IS NOT TO BE IN DIRECT CONTACT WITH EXOAIR 110AT. APPLY DYMONIC 100 BETWEEN THE MATERIALS.
7. ROOF ASSEMBLY AND CAP FLASHING ARE INSTALLED IN THE FIELD AND NOT COMPONENTS OF THE PANEL SYSTEM.

The architecture, engineering, and design of the project using the Dryvit Tremco and USG products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit Tremco and USG specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit Tremco and USG to ensure you have the most recent version.



Dryvit Technical Support: 800-556-7752

Outsulite® Securock® ExoAir® 430 Panel System



Technical Support: 866-209-2404

Detail: Parapet Panel - Metal Coping

Drawn by: HDE

Checked by:

Scale: NTS

Date: 1/9/2023

File Name:

OSL SE430-13



www.tremcocpg.com