



AIR BARRIER SELECTION GUIDE

Class 1 Vapor Retarder /
Impermeable

Vapor Permeable

Days UV-Resistant

High Temperature

Cold Temperature
Application

NFPA 285

Primerless

TYPE	PRODUCT	Class 1 Vapor Retarder / Impermeable	Vapor Permeable	Days UV-Resistant	High Temperature	Cold Temperature Application	NFPA 285	Primerless
Sheet Membrane	ExoAir 110AT®	•		365	•	•	•	•
	ExoAir 210AT®		•	180	•	•	•	•
Fluid Membrane	ExoAir® 120	•		30		• ¹		•
	ExoAir® 130	•		365	•		•	•
	ExoAir® 220		•	180			•	•
	ExoAir® 230		•	365	•		•	•
	ExoAir® 230 LT		•	365	•	•	•	•
Factory-Applied Membrane	ExoAir® 430		•	365	•	•	•	•
Flashing of the Rough Opening	Dymonic® 100			365	•		•	•
	ExoAir® 110	•		30				
	ExoAir® 110AT	•		365	•	•	•	•
	ExoAir® 230 & Mesh		•	365	•		•	•
Fluid Membrane	Dryvit Backstop® NTX		•	180		•	Only w/ Dryvit EIFS	•
	Dryvit Backstop® NT VB	•		180			Only w/ Dryvit EIFS	•
	Enviro-Dri®		•	120		•		•
Accessories	ExoAir® 110	•		30				

¹ Can be applied at cold temperatures with a co-spray.

* This guide is to be used as a general reference. Please consult your local Tremco Representative for regional recommendation based on your local building practices and warranty requirements.

Reference the current product data sheet on our websites for more specific product information:

Tremco products: www.tremcosealants.com

Dryvit products: www.dryvit.com



AIR BARRIER SELECTION GUIDE

Mil Thickness
 Grades: R: Roller,
 S: Spray, T: Trowel
 Compatible With
 Dryvit EIFS

Recommended Substrates

TYPE	PRODUCT	Mil Thickness	Grades: R: Roller, S: Spray, T: Trowel	Compatible With Dryvit EIFS	Recommended Substrates
Sheet Membrane	ExoAir 110AT®	22			CMU, concrete, metal, sheathing, wood sheathing, OSB, plywood
	ExoAir 210AT®	21			CMU, concrete, metal, sheathing, wood sheathing, OSB, plywood
Fluid Membrane	ExoAir® 120	40 Dry	R, S		CMU, concrete, metal, sheathing, wood sheathing, OSB, plywood
	ExoAir® 130	40 Dry	R, S		CMU, concrete, metal, sheathing, wood sheathing, OSB, plywood
	ExoAir® 220	40 Dry	R, S		CMU, concrete, metal, sheathing, wood sheathing, OSB, plywood
	ExoAir® 230	25-35 Dry	R, S	•	CMU, concrete, metal, sheathing, wood sheathing, OSB, plywood, Nudura ICF
	ExoAir® 230 LT	25-35 Dry	R, S	•	CMU, concrete, metal, sheathing, wood sheathing, OSB, plywood, Nudura ICF
Factory-Applied Membrane	ExoAir® 430	20 Dry		•	N/A
Flashing of the Rough Opening	Dymonic® 100	40 Wet		•	CMU, concrete, metal, sheathing, wood sheathing, OSB
	ExoAir® 110	40			CMU, concrete, metal, sheathing, wood sheathing, OSB
	ExoAir® 110AT	22			CMU, concrete, metal, sheathing, wood sheathing, OSB
	ExoAir® 230 & Mesh	35 Dry		•	CMU, concrete, metal, sheathing, wood sheathing, OSB
Fluid Membrane	Dryvit Backstop® NTX	12 Dry	R, S, T	•	CMU, concrete, metal, sheathing, wood sheathing, OSB
	Dryvit Backstop® NT VB	24 Dry	R, S, T	•	CMU, concrete, metal, sheathing, wood sheathing, OSB
	Enviro-Dri®	9 Dry	R, S		Glass-mat faced gypsum, plywood, OSB, structural fiberboard sheathing

Tremco | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Dryvit | 3735 Green Road | Beachwood, OH 44122 | 401.822.4100 | dryvit.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.



Tremco®, ExoAir®, Dymonic®, and Enviro-Dri® are registered trademarks of Tremco Incorporated. Dryvit® and Backstop® are registered trademarks of Dryvit Systems, Inc. Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.