

ENGINEERED FRAMING SYSTEM BY PREBUCK LLC OR FUNCTIONAL EQUIVALENT

TREMCO ROOF ASSEMBLY OR FUNCTIONAL EQUIVALENT, BY OTHERS

EXTEND OVER TOP OF PARAPET AND FASTENED TO OPPOSITE FACE

METAL CAP FLASHING, BY OTHERS

DRYVIT/TREMCO APPROVED TRANSITION MATERIAL (SEE NOTE 1)

CASING BEAD WITH WEEP HOLES, BY OTHERS

APPROVED SUBSTRATE, BY OTHERS

DRYVIT/TREMCO AIR/WATER-RESISTIVE BARRIER

PAPER BACKING, BY OTHERS

METAL PLASTER BASE AS SPECIFIED, BY OTHERS

STUCCOAT ONE COAT BASE, 3/8" MIN.

OPTIONAL STANDARD REINFORCING MESH EMBEDDED IN STUCCOAT CRACK ISOLATION MEMBRANE, AS SPECIFIED OR REQUIRED

OPTIONAL DRYVIT PRIMER, AS SPECIFIED OR REQUIRED

DRYVIT FINISH

NOTE:

1. REFER TO PRODUCT DATA SHEETS FOR SPECIFIC APPLICATION METHODS.

2. WALL ASSEMBLY SHALL PROVIDE FOR A MAXIMUM DESIGN DEFLECTION OF L/360.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

StucCoat One Coat® System



Dryvit Technical Support: 800-556-7752

Detail: Termination at Parapet - Cap Flashing

Drawn by: KAB

Checked by: BD/CB

Scale: NTS

Date: 4/2023

File Name:

SCOC 15



Construction Products Group

www.tremcocpg.com