

NOTES:

- MAXIMUM EPS INSULATION THICKNESS IS 3. FASTENERS ARE NOT REQUIRED FOR DICTATED BY LOCAL CODE AUTHORITY AND APPLICABLE TESTING. REFER TO **EVALUATION REPORTS FOR ANY** LIMITATIONS TO EPS THICKNESS.
- 2. DRYVIT GENESIS® OR GENESIS DM BASE COAT IS REQUIRED FOR MECHANICALLY **FASTENED SYSTEMS 1-3.**
- SYSTEMS 4 OR 5.
- PROVIDE TEMPORARY MEANS OF SUPPORT WHEN REQUIRED.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

Outsulation® RMD System™



Detail: EPS Shapes Checked by: KK Drawn by: HDE Scale: NTS Date: 5/19/2023 www.tremcocpg.com

O-RMD 43

File Name:

